

Airport Rescue and Firefighting Vehicle





Engine type / Power	Scania DC16 / 566 kW (770 HP)	
Drive / Performance	Permanent $4 \times 4 / 0 - 80$ km/h in < 20 sec, V_{max} 120 km/h	
Transmission	Continously (stepless), fully automatic	
Wheelbase	4,750 mm	
Max. GVW / Axle load	26,000 kg / 13,000 kg	
Vehicle dimension	L×W×H: 10,200 × 3,000 × 3,700 mm	
Norms / Standards	ICAO, EASA, NFPA, ADV, EC, CCCF	
Cabin / Crew	ZIEGLER security cab Z-Cab AiR / up to 1+5	
Superstructure	ALPAS of the latest generation	
Centrifugal fire pump	 ZIEGLER FPN 10-6000, PTO-driven 	Pump optionally made from bronze
	 Optional FPN 10-8000, PTO-driven 	 Stainless steel piping optional
Mixing system	ZIEGLER EAD	
Water tank	6,000 l; corrosion resistant GRP material	
Foam tank	800 l; corrosion resistant GRP material	
Turret	Bumper turret ZT-2000, optionally lowerable	
	 Roof turret ZT-6000 (series), ZT-8000 (optional) 	
Additional extinguishing systems	High-pressure pump	 120 kg CO₂ system
	 250 kg dry powder system 	• CAFS
	 Rapid intervention units 	
Special equipment	Assistance systems (Roll over prevention, navigation unit)	Light mast
	 Camera systems (IR, color, BirdView, mirror replacement) 	 Handhelds for turret operation
	 Additional lights (working, environment, flashing) 	Automatic foldable guardrail on roof

Illustrations may contain accessories and/or special equipment that are not part of the standard scope of delivery or service. Technical changes reserved. We cannot accept any liability for printing errors.



Albert Ziegler GmbH

Albert-Ziegler-Strasse 1 89537 Giengen/Brenz

Germany

Phone +49 (0)7322 951-0 Fax +49 (0)7322 951-211

info@ziegler.de



