


FPN 10-4000-2A





| Pump type | Art. no. | Engine | Pump output max. at 10 bar HS 3,0 m I/min | Weight approx. | Dimensions approx. LxWxH mm |
|---------------|----------|--|--|----------------|-----------------------------------|
| FPN 10-4000-2 | 1024453 | Mercedes-Benz Diesel engine Type OM 904 LA engine with 4 cylinders in line turbo-charged and charge-cooled water-cooled, 129 kW (175 HP) electric starter battery 12 V/88 Ah generator 28 V/80 A fuel tank approx. 100 l | 4200 | 1260 | 2870x1000x1750 |

Basic equipment

2stage centrifugal fire pump,

2 suction inlets size A, 4 delivery outlets size B with self-closing DIN-screw down valves, suction inlets and delivery outlets with blank cap.

Priming system: fully automatic TROKOMAT PLUS with cover

Auxiliary equipment and systems

on request, additionally charged:

suction inlet respectively delivery outlets on customer request automatic pressure governor (TOURMAT), single axle platform trailer acc. to art. no. 1010155.

Gauges and controls

Pressure gauge and mano-vacuummeter.

All instruments and switches for engine operation and control are integrated in an instrument box.

Pump drive

via joint shaft and electromagnetic clutch

Paintwork

basic frame black pump silver coloured RAL 9006 cover red RAL 3000

